



Index

Access channel	6.1.2.2
Aesthetic properties	3.3.1
Ageing – structure	10.1.1.2, 10.2.2
Ageing – unit	10.1.1.2
Angle of internal friction	5.2.1.3, 5.2.3.5, 5.2.4.3, 5.4.2.7, 5.4.3.5, 5.4.4.2, 5.4.4.5
Angle of repose	5.2.1.3, 5.2.3.1, 5.2.3.5, 5.4.4.2
Armour function	3.1.2.1, 3.1.3.2
Armour layer	2.3.2.1, 5.2.1.2, 5.2.2, 6.1.4.1, 6.2.3.5, 6.3.3.5, 9.7.2.2, 9.7.2.3
Armourstone – integrity	3.3.4, 3.6.6, 3.8.5.2
Armourstone – major breakage	3.6.6, 3.8.5.2
Armourstone – manufactured	3.1.2.2
Armourstone – measuring	3.8
Armourstone – natural	3.1.2.2
Armourstone – recycled	3.1.2.2
Armourstone – sampling	3.8
Armourstone – specification	3.7
Armourstone – testing	3.8
Armourstone properties – execution-induced	3.1.2.2, 3.5
Armourstone properties – intrinsic	3.1.2.2, 3.3
Armourstone properties – production-induced	3.1.2.2, 3.4
Armourstone shape	5.2.1.2, 5.2.2.2
Asset management	2.1
Atmospheric pressure data	4.2.1.2
Bank protection	1.5.2, 9.7.1.3
Banks type	8.2.1
Barrages	7.5.4
Barriers	7.5.2
Basin storage model	4.2.3.3
Bastion groyne	6.3.4.3, 6.3.1.3
Bathymetry	4.1.1.1, 4.1.1.2, 4.1.2, 4.1.3
Beaches	4.1.2.4
Bed protection	1.5.2, 9.7.1.2
Bed protection – closure works	7.2.2, 7.2.5, 7.2.6
Bed protection (currents)	5.2.3.1
Bed shear stress	4.3.2.6
Berm	2.3.2.1, 5.1.1.2, 5.1.1.3, 5.2.2.6
Berm or S-slope breakwater	5.2.2.6, 6.1.1.2, 6.1.6
Berm recession	5.2.2.6, 6.1.6
Berth protection	6.1.2.1, 6.2
Bituminous bound materials	3.15.2
Blasted block size distribution	3.9.1, 3.9.3, 3.9.4
Blasting	3.9.3
Blockiness	3.4.1.2
Bottom friction	4.2.4.7
Breakage	3.6.6, 3.3.4, 3.8.5.1

Breakwater	1.5.2, 6.1
Breakwater – crest freeboard	6.1.4.1
Breakwater – crest width	6.1.4.1
Breakwater – crown wall	6.1.1.2, 6.1.5
Breakwater – layer thickness	6.1.4.2
Breakwater – roundhead	6.1.4.1
Breakwater – shoulder	6.1.4.2
Breakwater – slope angle	6.1.4.1
Breakwater – toe	6.1.4.2
Breakwater roundheads	5.2.2.13, 5.3.2.1
Breakwaters	9.7.2.1
Bridge piers	8.5.3
Bridge scour protection	1.5.2
Bulk (or placed packing) density	3.5.1 , 5.2.1.1, 5.2.4.3, 5.4.3.5, 5.4.3.6, 9.8.1.1
Bunds	9.7.3
Caisson-type breakwater	6.1.1.2, 6.1.3.4, 6.1.7
Channel width	4.1.3.3, 4.3.1.1
Chézy	4.3.2.3
Cliff/dune toe protection	6.3.4.4
Cliffs and shore platforms	4.1.2.6
Coastal dunes	4.1.2.5
Cofferdams	7.3.5
Component	2.2.1.2, 2.3.2.1
Composite breakwater	6.1.1.2, 6.1.7
Composite cross-section	4.3.2.3
Composite slopes	5.2.2.8
Composite systems	5.2.2.7
Concept design	2.2.1.1, 2.2.1.4
Concrete	3.12.1.4, 3.12.3.2
Concrete armour units	3.12, 5.2.2.3, 9.7.2.6
Concrete gravity structure	9.7.4.1
Concrete grouts	3.15.1
Construction	2.2.1.1, 2.2.1.4
Construction risks	9.5.3.5
Controlled placement	9.3.2, 9.3.3, 9.3.6.2, 9.7.4.2
Core	2.3.2.1, 9.7.2.2, 9.7.2.3
Core material	3.4.4
quarry run	3.4.4.1
tout venant de carrière	3.4.4.1
crusher run	3.4.4.1
all-in	3.4.4.1
Costs	2.4, 10.1.2
Costs – armourstone	3.11
Costs – construction	2.4.5
Costs – fixed	2.4.2

Costs – maintenance and repair	2.4.6
Costs – materials	3.1.1.6
Costs – removal	2.4.7
Costs – sourcing and production	2.4.4
Costs – transportation	2.4.4
Costs – variable	2.4.2
Crest	2.3.2.1
Crest design	6.1.4.2, 6.3.4.2
Crest stability	5.2.2.11
Critical shear stress	5.2.1.1, 5.2.1.3, 5.2.1.8
Critical velocity	5.2.1.1, 5.2.1.4, 5.2.1.8, 5.2.3.2, 5.2.3.3, 5.2.3.5
Critical wave overtopping discharges	5.1.1.3
Crown element	9.7.2.1
Crown wall	2.3.2.1, 5.2.2.12
Cubicity	3.4.1.3
Dam porosity	5.1.2.3, 5.2.1.2, 5.2.3.5
Damage – armour quality defects	10.4.3.1
Damage – armourstone loss	10.4.3.1
Damage – breach/loss of crest elevation	10.4.3.1
Damage – core (or underlayer) exposure or loss	10.4.3.1
Damage – slope defects	10.4.3.1
Damage level (parameter)	5.2.1.2, 5.2.2.2, 5.2.2.3, 5.2.2.4, 5.2.2.5, 5.2.2.9, 5.2.2.11, 5.2.2.13
Damage number	5.2.1.2, 5.2.2.3, 5.2.2.9
Damage percentage	5.2.1.2, 5.2.2.2
Data management	10.3.2.5
Decommissioning	2.2.1.1
Deep water waves	4.2.4.4, 4.2.4.5
Degradation	3.6
Degradation – structure	10.1.1.2, 10.3.4.2
Degradation – units	10.3.4.2
Design – information needs	2.2.2.1
Design approaches	2.3.3.3
Design conditions	10.5.1.1
Design criteria	2.3.3.2
Design cycle	2.2.1.3
Design life	2.3.3.2
Design process	2.1.1, 2.3.3.1
Detailed design	2.2.1.1, 2.2.1.4
Deterministic	2.3.3.3
Diameter	3.4.2
Diffraction	4.2.4.7
Discharge coefficient	5.1.2.3, 5.2.3.2, 5.2.3.5, 5.3.3.2
Discontinuities	3.2.2
Dissipation	4.2.4.7

Diversion dams	7.5.5
Drop test	3.8.5.2
Durability	3.1.3, 3.6, 3.8.6
Dutch toe	6.3.4.1
Dynamically stable	5.2.1.2, 5.2.2.1, 5.2.2.4, 5.2.2.6, 5.2.2.13
Dynamically stable reshaping	6.1.6
Earthfill dams	7.4.4
Earthquake resistance	5.4.3.5
Ecology	3.1.1.5
Element	2.2.1.2
Emergency repairs	9.7.6
Emergent structures	5.2.2.1, 5.2.2.4
Environment	3.1.1.5
Environmental enhancement	2.5.3
Environmental Impact Assessment	2.5.4
Environmental impacts	2.5.1
Equilibrium river depth	4.3.2.4
Equipment	9.3
Land based equipment	9.3.2, 9.3.3
Waterborne equipment	9.3.4, 9.3.5
Erosion	2.3.1
Escameia and May formula	5.2.3.1
Estuaries	4.1.3.2, 4.2.3.3
Estuary closures	1.5.2, 7.2
European Standard EN13383	3.2.3, 3.7
Failure (modes)	5.2.2.12, 5.2.4.2, 5.2.4.3, 5.4.1, 5.4.3
Failure modes	6.1.3.4
Failure modes/mechanisms	2.3.1
Failure of concrete armour layers	5.2.2.3
Failure of rock-armoured structure	5.2.1.2, 5.2.2.2, 5.2.2.9
Fascine mattress	8.1.3.7
Fetch	4.2.4.6
Fictitious wave steepness	4.2.4.3, 5.1.1.1
Filter function	3.1.2.1, 3.1.3.2
Fish passes	1.5.2, 8.5.2
Flexible fall pipe	9.3.1, 9.3.5, 9.3.6.2, 9.7.4.1
Flood plain	4.3.1.1
Flood protection	8.2.2.6
Flood waves	4.2.2.9, 4.3.3
Fragments	3.4.3.5
Froude number	5.1.2.3, 5.2.3.5, 5.3.2.1, 5.3.2.2
Full scale splitting test	3.6.6.3
Gabion revetment	5.2.2.7
Gabions	3.14, 8.6.2
Geotechnical investigation	4.4

- Geotextiles/geotextile filters 3.16 , 5.2.2.2, 5.2.2.3, 5.2.2.10,
. 5.2.3.4, 5.4.3.6, 5.4.4.5, 6.3.3.6, 6.3.4.1, 6.3.4.4
- Grab 9.3.3, 9.7.2.2, 9.8.1.1
- Gradation. 3.4.3.1, 5.2.1.2, 5.2.2.2, 5.2.2.6
- Grading curves. 3.4.3
- Grading width. 3.4.3.1
- Grading(s) 3.4.3, 3.8.4.2, 5.2.1.2, 5.2.2.2, 5.2.2.3, 5.2.2.9
- Gradings – non-standard 3.4.3.9
- Gradings – standard 3.4.3
- Gradual closure 7.2.2, 7.2.6
- Granular filters 5.2.2.2, 5.2.2.3, 5.2.2.7, 5.2.2.10, 5.2.3.4, 5.4.3.6
- Grouted stone 5.2.2.7, 5.2.3.1, 8.6.1, 6.2.4
- Grouts 3.15.1, 3.15.2.3
- Groyne – fishtailed 6.3.1.5, 6.3.2.2, 6.3.4.4
- Groyne – L-shaped. 6.3.1.6, 6.3.2.2, 6.3.4.4
- Groyne – T-shaped 6.3.1.6, 6.3.2.2, 6.3.4.4
- Groynes. 1.5.2, 6.3.1.3, 6.3.2.2, 6.3.4.4
- Guide banks 8.2.2.4, 8.2.4.4, 8.2.4.5
- Hard points. 8.2.4.2
- Health and safety 2.6.1, 9.2.1.2, 9.4.1, 9.5.1, 9.5.3.2
- Horizontal closure 7.2.3
- Horizontal closure method 5.1.2.3, 5.2.3.5
- Horizontal river closures 7.3.6
- Hudson formula 5.2.2.2, 5.2.2.3
- Hydraulic roughness 4.3.2.3
- Hydrographs. 4.3.3.2
- Hydrology 4.3.2.2
- Hysteresis 4.3.1.2
- Ice 4.5
- Ice structure interaction. 5.2.4.1, 5.2.4.2, 5.4.2.3
- Icelandic-type berm breakwater. 5.2.2.6
- In situ* block size distribution 3.9.1, 3.9.2
- Instantaneous closures. 7.2.5
- Integrated design 2.2.1.4
- Intermediate damage 5.2.1.2, 5.2.2.2, 5.2.2.3, 5.2.2.4
- Iribarren number 4.2.4.3
- Izbash and Khaldre formula 5.2.1.4
- Izbash number or Izbash parameter 5.2.1.1, 5.2.1.2, 5.2.1.8, 5.2.1.9
- Joint probability. 4.2.5
- Joints and transitions. 6.1.4.3, 6.3.4.3
- Keulegan-Carpenter number. 5.4.4.4
- Laminar flow 5.1.2.2, 5.4.3.6, 5.4.4.4
- Land-based operations 9.3.1, 9.3.6.1, 9.3.7, 9.7.2.2
- Layer (or volumetric) porosity 5.1.2.2, 5.1.2.3, 5.2.1.2, 5.2.2.2, 5.2.2.3, 5.2.2.12, 5.2.3.5,
- Layer porosity. 9.8.1.2, 9.8.2, 9.8.4

Layer thickness	3.5.1 , 5.2.1.2, 5.2.2.3, 5.2.2.7, 5.2.2.9, 5.2.3.1, 5.2.3.3, 5.2.4.3, 5.4.5.2, 5.4.5.3
Length to thickness ratio.	3.4.1.1, 3.8.4.1
Levees	4.3.1.1
Lifecycle management	10.1.1
Liquefaction	2.3.1
Loading	2.3.2.2
Loading facilities	9.2.2.1
Local and secondary currents	4.3.2.4
Local instability	2.3.1
Longitudinal dikes	1.5.2
Longitudinal slope angle	4.3.1.1
Long-period waves	4.2.2.7
Low-cost structures	6.3.1, 6.3.5
Low-crested structures	5.2.2.1, 5.2.2.4
Macro scale	2.2.1.2
Maintenance interval	10.2
Maintenance policy	10.1.2
Management options	10.4.4
Management strategy/plan	10.2
Manning – Strickler	4.3.2.3
Marine currents	4.2.3
Mass density	3.3.3.2, 3.8.2.3
Mass distribution.	3.4.3, 3.8.3.2
Material functions	3.1.2.1
Maynard formula	5.2.3.1
Mean sea level.	4.2.2.1
Mean, peak and energy wave period.	5.1.1.1
Meandering.	4.1.3.3
Meso scale	2.2.1.2
Micro scale	2.2.1.2
Migration of materials	2.3.1
Mobility	5.2.2.6
Mobility parameter.	5.2.1.1, 5.2.1.5, 5.2.2.5, 5.2.3.1, 5.3.2.2
Modelling of water levels and currents – numerical models	4.3.5.1, 4.3.5.2
Modelling of water levels and currents – physical models.	4.3.5.1, 4.3.5.3
Modelling waves – numerical models	4.2.4.10
Modelling waves – physical models	4.2.4.10
Monitoring	10.3, 10.4.1
Monitoring – condition.	10.3.2.2
Monitoring – condition-based monitoring	10.3.3
Monitoring – environment.	10.3.2.4
Monitoring – performance	10.3.2.3
Monitoring – periodic inspection	10.3.3
Monitoring – use-based inspection	10.3.3

Monitoring interval	10.3.3
Morphology	4.1.1.1, 4.1.1.2, 4.1.2, 4.1.3
Mountainous rivers	8.4
Movement of elements	2.3.1
Muddy shorelines	4.1.2.3
Multi-layer berm breakwater	6.1.6.1
Navigation canals	8.3.2.1, 8.3.4.2
Navigation works	8.2.2.5
Near-bed structures	5.2.2.1, 5.2.2.5, 5.2.3.2
Neural network modelling	5.1.1.3
Non-overtopped structures	5.2.2.1, 5.2.2.2
Non-woven geotextiles	3.16
Notional permeability factor	5.1.1.2, 5.1.1.4, 5.2.1.2, 5.2.2.2
Numerical modelling of marine currents	4.2.3.4
Offshore bed protections	9.7.4.1
Offshore or detached breakwaters	6.3.1.4, 6.3.2.2, 6.3.4.4
Offshore pipeline covers	9.7.4.2
Offshore structures – protection of pipelines and cables	6.4.1, 6.4.1.1
Offshore structures – scour protection	6.4.1, 6.4.1.2, 6.4.1.3
Open piled jetties	6.2.3.3
Operation	2.2.1.1
Orbital velocity	5.2.1.1, 5.2.1.3, 5.2.1.8, 5.2.2.5
Overtopping damage	2.3.1
Overtopping of crown wall	6.1.5
Overtopping volumes per wave	5.1.1.3
Packing	9.8.1.1, 9.8.1.2
Packing (density)	3.4.1.2, 3.4.4, 3.5.1, 3.12.1.3, 3.12.2.5, 3.12.3.5, 5.2.1.2, 5.2.2.2, 9.8.2, 9.3.3
Packing and placement	5.2.1.2, 5.2.2.2
Packing density coefficient	3.12.1.3, 3.12.2.5, 5.2.1.2, 5.2.2.3
Packing factor (Knauss)	5.2.3.5
Perched beach	6.3.1.7
Performance level	10.1.1.2
Period (or dynamic) stability number	5.2.2.1, 5.2.2.6
Permeability	5.1.1.2, 5.1.1.3, 5.1.1.4, 5.1.2.2, 5.1.2.3, 5.2.1.2, 5.2.2.2,
Permeable structures	5.1.1.2
Petrography	3.3.2, 3.8.2.2
Pilarczyk formula	5.2.3.1
Pipeline protection	1.5.2
Piping	2.3.1, 5.4.3.6
Pitched stone	8.1.3.7
Placed packing (or bulk) density	3.5.1, 9.8.1.1
Placing	9.8.1.1, 9.8.1.2
Plunging waves	5.1.1.1, 5.1.1.3, 5.2.2.2, 5.2.2.3, 5.2.2.7
Pore pressures	5.4.3.5, 5.4.3.6, 5.4.3.8, 5.4.5.1, 5.4.5.2, 5.4.5.3

Porosity	3.3.3.2
Port structures	1.5.2
Port structures	6.2
Preliminary design	2.2.1.1, 2.2.1.4, 3.1.1.7
Primary ship wave	4.3.4
Probabilistic	2.3.3.3, 5.2.2.2
Procurement	3.1.1.4
Project – planning.	3.1.1.2
Project – scale	3.1.1.1
Project definition	2.2.1.1, 2.2.1.4
Project process	1.3.2
Propeller jets	4.3.4.3, 5.2.3.1, 6.2.3
Quality control	9.2.1.2, 9.8.1, 9.8.3.1, 9.8.3.2
Quality control – armourstone.	3.1
Quality control – concrete armour units	3.12.3.4
Quarries – aggregate	3.9
Quarries – dedicated	3.9
Quarries – dimension stone	3.9
Quarry – evaluation.	3.2.3
Quarry – handling.	3.9.8
Quarry – layout	3.9.6
Quarry – processing	3.9.7
Quarry – selection	3.9.7
Quarry – sorting	3.9.7
Quarry – transport	3.9.8
Quay walls – toe protection	6.2.1.1, 6.2.3
Radiation stress.	4.2.2.5
Radius of roundhead	5.2.2.13
Rear-side stability	5.2.2.11
Reclamation protection.	6.3.4.4
Recycled materials	3.13
Refraction	4.2.4.7
Regime theory.	4.1.3.4
Regular waves	4.2.4.2
Rehabilitation	10.2, 10.5.2, 10.5.4
Rehabilitation – armour layers	10.5.4.1, 10.5.4.2
Relative buoyant density.	5.1.2.3, 5.2.1.1, 5.2.1.2, 5.2.1.3, 5.2.2.2, 5.2.2.3, 5.2.2.4,
Repair	10.2, 10.5.1.2, 10.5.2, 10.5.3
Repair – armour layers.	10.5.3.1
Repair – armour units	10.5.3.2
Repair – spot repairs	10.5.3.2
Repair – toes and berms.	10.5.3.3
Repair – voids.	10.5.3.3
Repair areas	9.2.1
Reservoir dam.	1.5.2, 7.4

Reshaping structures	5.2.2.6
Return current	4.3.4.1, 5.2.2.2, 5.2.3.1
Return period	2.3.3.2
Revetment	1.5.2, 6.3.1.1, 6.3.2.2, 6.3.4.4, 8.2.2.2, 8.2.4.2, 8.2.4.5, 8.4.4
Revetment slope	8.2.5.3
Revetment toe	8.2.6.3
Revetment transition zones	8.2.6.7
Reynolds number(s)	5.1.2.2, 5.2.1.3, 5.3.2.2
Rip-rap or riprap	3.4.3.1
Risk management	9.7.3
River – discharge	4.3.1.2; 4.3.2.1 – 2 – 3
River – energy	4.3.1.2
River – geometry	4.3.1.1
River – hydraulic radius	4.3.1.1
River – turbulence intensity	4.3.2.5
River – velocity distribution	4.3.2.4
River – water depth	4.3.1.1
River – water level	4.3.1.2
River – water surface	4.3.1.1
River – wetted perimeter	4.3.1.1
River alignments	9.7.5.2
River bends	4.3.2.4
River bifurcations	4.3.2.7
River closure	1.5.2, 7.3
River closure bunds	7.3.5
River confluences	4.3.2.7
River protection works	9.7.5
River training works	8.2
Rivers	4.1.3.3, 4.3
Rock berm	6.4.3
Rock sources	3.1.1.4
Rock types	3.2.2
Rockfill closure dams	1.5.2, 5.2.3.5, 7.4.5
Roundhead	2.3.2.1, 6.3.4.4, 6.1.4.1
Roundness	3.4.1.4, 5.2.2.2
Rubble mound breakwater	6.1.1.2, 6.1.3.4, 6.1.4.1
Safety	9.7.3.2
Salient	6.3.2.2, 6.3.1.4
Sand waves	4.1.2.2
Saturation	3.3.3.2, 3.3.3.3
Scour protection	1.5.2, 2.3.2.1, 5.2.2.9, 5.2.3.3, 6.3.1.2, 6.3.2.2, 6.3.4.1, 6.3.4.4
Sea level rise	4.2.2.10
Sea-state	4.2.4
Seawalls	1.5.2, 9.7.3, 9.9.3
Secondary materials	3.13

Secondary ship waves	4.3.4.2
Seepage flow (velocity)	5.1.2.2, 5.4.3.6, 5.4.4.4
Seiches	4.2.2.6
Sensitivity analysis	2.3.3.3, 5.2.2.2
Service levels	10.1.1.1
Serviceability limit state (SLS)	5.4.2.3, 5.4.3.1, 6.1.3.4
Settlement	2.3.1, 5.4.3.7
Shallow water waves	4.2.4.4, 4.2.4.5, 4.2.4.7
Shallow-water conditions	5.2.2.2, 5.1.1.3
Shape	3.4.1, 3.8.3.1, 3.8.4.1
Shear velocity	5.1.2.2, 5.2.1.1, 5.2.1.3, 5.3.2.2
Shields parameter	5.2.1.1, 5.2.1.2, 5.2.1.3, 5.2.1.9, 5.2.3.1, 5.2.3.2, 5.2.3.5
Ship induced water movements	4.3.4
Ship-induced waves	4.3.4, 5.2.2.2
Shoaling	4.2.4.7
Shoulder width in shallow water	6.1.4.2
Side stone-dumping vessel	9.3.5, 9.3.7, 9.7.2.3
Sill	6.3.1.7, 6.3.2.2, 6.3.4.4, 7.5.3
Site	9.2
Site constraints	3.1.1.5
Size distribution	3.4.3, 3.8.3.2
Skewness of waves	5.2.2.2
Sliding	2.3.1
Slope design	6.3.3.4
Slope instability	2.3.1, 5.4.3.2
Slope protection	5.2.3.1, 5.2.4.3, 5.2.4.4
Slope protection under piled deck	6.2.3.9, 6.2.6
Sonic velocity	3.8.6.1
Specific discharge	5.1.1.3, 5.1.2.1
Specification – armourstone	3.7, A1
Specification – geotextiles	3.16.5, A1
Spur-dykes	1.5.2, 8.2.2.3, 8.2.4.3, 8.2.4.5, 9.7.5.2
(Static) Stability number	5.2.1.1, 5.2.1.2, 5.2.2.1, 5.2.2.2, 5.2.2.3,
Stakeholders	1.4, 2.6.3
Start of damage	5.2.1.2, 5.2.2.2, 5.2.2.3, 5.2.2.4, 5.2.2.8, 5.2.2.9
Statically stable non-reshaping	5.2.2.6, 6.1.6
Statically stable reshaping	5.2.2.6, 6.1.6
Stepped slopes	5.2.2.8
Stockpile areas	9.2.1
Stone demand versus quarry yield	6.1.8.1, 6.3.5
Storm surges	4.2.2.3, 4.2.2.12
Streams	8.4
Structure condition – evaluation	10.4, 10.4.3
Structure performance – evaluation	10.4.2
Subcritical flow	5.1.2.3, 5.2.3.5

Submerged breakwater	6.3.1.7, 6.3.2.2, 6.3.4.4
Submerged structures	5.2.2.1, 5.2.2.4
Supercritical flow	5.1.2.3, 5.2.3.5
Surf-similarity parameter or breaker parameter or Iribarren number	4.2.4.3, 5.1.1.1, 5.2.2
Surging waves	5.1.1.1, 5.1.1.3, 5.2.2.2, 5.2.2.3
Survey – above water	10.3.4
Survey – bathymetry	10.3.5.1
Survey – photogrammetry	10.3.4.3
Survey – photography	10.3.4.3
Survey – remote sensing	10.3.5.3
Survey – side scan sonar	10.3.5.2
Survey – single/multi-beam	10.3.5.1
Survey – sub-bottom	10.3.5.4
Survey – underwater	10.3.5
Survey – underwater visual inspection	10.3.5.5
Survey techniques	9.5.9
Conventional staff	9.9.8.1
Highest points	9.9.8.1
Multi-beam	9.9.8.2
Single-beam	9.9.8.2
Spherical foot staff	9.9.8.1
Sustainability	2.5.1
Swell	4.2.4
System	2.2.1.2
Tailwater parameter	5.1.2.3, 5.2.1.2, 5.2.3.5
Terminal groyne	6.3.2.2, 6.3.4.3
Through-flow	5.1.2.3, 5.2.1.8, 5.2.3.5
Tide	4.2.2.2, 4.2.2.12
Tilting	2.3.1
Toe protection (design)	2.3.2.1, 5.2.2.9, 5.2.3.3, 6.1.4.2, 6.3.4.1, 8.2.7.3, 9.7.2.2, 9.7.2.3
Tolerances	9.3.7
Tombolo	6.3.2.2
Topography	4.1.1.1
Transitions	6.1.4.3, 8.2.7.6
Translation waves	4.3.3.3
Transport of armourstone	9.4
Rail transport	9.4.2
Road transport	9.4.1
Transshipment to the shore	9.4.3.2
Waterborne transport	9.4.3.1
Tsunami	4.2.2.8
Turbulence	5.1.2.1, 5.2.1.3, 5.2.1.4, 5.2.1.8, 5.2.1.9, 5.2.3.1, 5.2.3.2, 5.2.3.5, 5.3.3.2
Turbulent flow	5.1.2.2, 5.2.1.3, 5.3.2.2, 5.4.4.4
Ultimate limit state (ULS)	5.4.2.3, 5.4.3.1, 6.1.3.4
Underlayer	2.3.2.1, 5.2.2.10, 5.2.2.3, 6.1.4, 6.3.3.6, 9.7.2.2, 9.7.2.3

Unloading facilities	9.2.2.2
Ursell number	4.2.4.3
Van der Meer formula	5.2.2.2
Velocity profile factor or depth factor	5.2.1.8, 5.2.1.9, 5.2.3.1
Vertical closure method	5.1.2.3, 5.2.3.5, 7.2.3
Vertical river closures	7.3.7
Void (or layer) porosity	3.5.1
Volume filling function	3.1.2.1, 3.1.3.2
Water absorption	3.3.3.2
Water conveyance canals	8.3.2.2, 8.3.4.3
Water borne equipment	9.3.4, 9.3.5
Waterborne operations	9.3.1, 9.3.6.2, 9.3.7, 9.7.2.3
Wave – angular frequency	4.2.4.2
Wave – frequency	4.2.4.2
Wave – spectra	4.2.4.5
Wave – steepness	4.2.4.3
Wave – wave number	4.2.4.2
Wave by wave analysis	4.2.4.4
Wave climate	4.2.4.1, 4.2.4.8, 4.2.4.9
Wave climate – long-term wave climate	4.2.4.9
Wave climate – short-term wave climate	4.2.4.8
Wave height	4.2.4.1, 4.2.4.4, 4.2.4.5, 4.2.4.6, 4.2.4.7
Wave length	4.2.4.1, 4.2.4.2
Wave overtopping	6.3.3.3
Wave overtopping for smooth and rough slopes	5.1.1.3
Wave overtopping of rough slopes with crown walls	5.1.1.3, 5.2.2.12
Wave overtopping velocities	5.1.1.3
Wave period	4.2.4.1, 4.2.4.4, 4.2.4.5
Wave run-down	5.1.1.2
Wave run-up for shallow foreshores	5.1.1.2
Wave run-up on smooth slopes, rough slopes, bermed slopes and permeable structures	5.2.2.4, 5.2.2.6, 5.2.2.9
Wave set-up	4.2.2.5
Wave statistics	4.2.4.4
Wear	3.3.4
Weathering	3.2.2, 3.6
Weirs	7.5.4
Whole-life costing	2.4.1
Wind data	4.2.1.1
Wind set-up	4.2.2.4
Wind waves	4.2.4
Working conditions	9.3.6
Woven geotextiles	3.16
Yield curve	3.9.4